

7-13-00

A

07/12/00  
jc877 U.S. PTO

jc808 U.S. PTO  
09/614978  
07/12/00

Attorney Docket No.: TH1781 (US)  
A Named Inventor/Application Identifier: YE-MON CHEN  
Express Mail Label No.:  
Title: STANDPIPE INLET FOR ENHANCING PARTICULATE SOLIDS CIRCULATION FOR  
PETROCHEMICAL AND OTHER PROCESSES  
Date: July 12, 2000

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**UNDER 37 CFR 1.53(b)**

Assistant Commissioner for Patents  
Box Patent Applications  
Washington, DC 20231

1. ☒ This application is a(n):
  - a. ☐ Original
  - b. ☒ Continuation-in-part of Application Serial No. 09/253,859 filed February 22, 1999.
  - c. ☐ Divisional of Application Serial No. \_\_\_\_\_ filed \_\_\_\_\_  
☐ Applicant(s) elect the invention of Group/Species \_\_\_\_\_
  - d. ☐ Continuation of Application Serial No. \_\_\_\_\_ filed \_\_\_\_\_
  
2. ☒ Specification
  - a. ☒ Pages 17
  - b. ☒ Drawings, Total sheets 6
  
3. ☒ Oath or Declaration
  - a. ☐ Newly executed (original or copy)
  - b. ☐ Copy from a prior application  
☐ Please delete the following named inventors in the prior application: \_\_\_\_\_
  
4. ☒ Please amend the specification
  - a. ☒ By inserting before the first line:  
 This is a ☐ continuation ☐ division ☒ continuation-in-part of Application Serial No. 09/253,859 filed February 22, 1999, the entire disclosure of which is hereby incorporated by reference
  - b. ☐ By inserting before the first line:  
 This application claims the benefit of U.S. Provisional Application No. \_\_\_\_\_ filed \_\_\_\_\_, the entire disclosure of which is hereby incorporated by reference
  - c. ☐ Cancel claims \_\_\_\_\_
  
5. ☐ This application claims the benefit of Application Number \_\_\_\_\_ filed on \_\_\_\_\_  
 \_\_\_\_\_ in \_\_\_\_\_ under 35 U.S.C. § 119, § 365(a), or § 365(b).  
 (For originals)

6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Recognize as an associate attorney \_\_\_\_\_, Registration No. \_\_\_\_\_
8. ☒ Address all future communications to:

Carl O. McClenny  
 Shell Oil Company  
 Legal – Intellectual Property  
 P. O. Box 2463  
 Houston, Texas 77252-2463

9. ☒ Fee Transmittal (duplicate enclosed)

(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
TOTAL CLAIMS (37 CFR 1.16(c))	25- 20 =	5	X \$18.00 =	\$90.00
INDEPENDENT CLAIMS (37 CFR 1.16(b))	2- 3 =	0	X \$78.00 =	
MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			+ \$260.00 =	
			BASIC FEE (37 CFR 1.16(a))	\$690.00
Total of above Calculations =				90.00
TOTAL =				\$780.00

10. ☒ Please charge Deposit Account No. 19-1800 in the amount of \$780.00.
11. ☒ The Assistant Commissioner is authorized to charge all additional required fees or to credit overpayments, to Deposit Account No. 19-1800, including fees required under 37 CFR 1.17
12. ☒ Accompanying Application Parts
- a. ☐ Recordal of Assignment and Assignment
  - b. ☐ Information Disclosure Statement/PTO-1449
  - c. ☐ Preliminary Amendment
  - d. ☒ A self-addressed, stamped return receipt postcard to be returned with the filing date and Serial No. thereon
  - e. ☐ Certified copy of priority documents

Respectfully submitted,

YE-MON CHEN

By Carl O. McClenny  
 Attorney, Carl O. McClenny  
 Registration No. 26,481  
 (713) 782-3620

P. O. Box 2463  
 Houston, Texas 77252-2463

5

## STANDPIPE INLET FOR ENHANCING PARTICULATE SOLIDS CIRCULATION FOR PETROCHEMICAL AND OTHER PROCESSES

10

### BACKGROUND OF THE INVENTION

#### Reference to Related Applications

This is a continuation-in-part of application S/N 09/253,859 filed February 22, 1999.

15

#### 1. FIELD OF THE INVENTION

20

The invention relates to a standpipe inlet design for enhancing particle circulation and reducing gas entrainment, the design being suitable for applications in fluid catalytic cracking (FCC) units and other processes, such as fluid cokers, flexicokers, and fluidized bed combustors which circulate large quantities of particulate solids between different vessels connected with standpipes and risers.

#### 2. DESCRIPTION OF THE RELATED ART

25

30

35

In a typical Fluid Catalytic Cracking (FCC) process consisting of a regenerator, a riser reactor and a stripper, such as that shown in US Patent No. 5,562,818 to Hedrick which is incorporated herein by reference, finely divided regenerated catalyst leaves a regenerator and contacts with a hydrocarbon feedstock in a lower portion of a reactor riser. Hydrocarbon feedstock and steam enter the riser through feed nozzles. The mixture of feed, steam and regenerated catalyst, which has a temperature of from about 200° C to about 700° C, passes up through the riser reactor, converting the feed into lighter products while a coke layer deposits on catalyst surface. The hydrocarbon vapors and catalyst from the top of the riser are then passed through cyclones to separate spent catalyst from the hydrocarbon vapor product stream. The spent catalyst enters the stripper where steam is introduced to remove hydrocarbon products from the catalyst. The spent catalyst containing coke then passes through a stripper standpipe to enter the regenerator where, in the presence of air and at a temperature of from about 620° C to about 760° C, combustion of the coke layer produces

regenerated catalyst and flue gas. The flue gas is separated from entrained catalyst in the upper region of the regenerator by cyclones and the regenerated catalyst is returned to the regenerator fluidized bed. The regenerated catalyst is then drawn from the regenerator fluidized bed through the regenerator standpipe and, in repetition of the previously mentioned cycle, contacts the feedstock in the reaction zone.

Catalyst circulation is critical to overall performance and reliability of FCC units. The main drive for catalyst circulation comes from stable and adequate pressure build-up in the standpipe. One critical element of the standpipe design is the inlet design because it determines the inlet condition of the catalyst which, in turn, affects the entire standpipe operation.

The prior art of standpipe inlet design, for both stripper standpipe and regenerator standpipe, is a conical hopper such as that shown in "Handbook of Petroleum Refining Process", second edition by R.A. Meyers, which is incorporated herein by reference. The key concept of the inlet hopper design of the prior art is that when catalyst particles are drawn from a fluidized bed into a standpipe, bubbles are also drawn together with the catalyst. The inlet hopper provides residence time for the bubbles to coalesce and grow into large bubbles before entering the standpipe. Since large bubbles have a higher riser velocity, they have a better chance to escape back into the fluidized bed, thus reducing gas entrainment into the standpipe.

However, the design concept of the prior art standpipe inlet has several disadvantages. If the inlet hopper is too small, many bubbles drawn into the inlet hopper do not have enough time to grow but flow directly into the standpipe, leading to high gas entrainment. If, on the other hand, when the inlet hopper is large enough to allow small bubbles to grow, large bubbles could form and hang stationary inside the hopper for a period of time as the bubbles try to rise against the downward catalyst flow. These large hanging bubbles can temporarily restrict catalyst flow into the standpipe. When the bubbles finally grow large enough to escape into the fluidized bed, the release of the large bubbles creates a sudden surge of catalyst into the standpipe, leading to a sudden pressure swing in the standpipe. The sequence of growing and releasing of large bubbles leads to a very undesirable condition of unstable standpipe operation. The fundamental flaw of the prior art design is that, while the objective of the standpipe inlet design is supposed to reduce gas entrainment into the standpipe, the design in fact encourages many bubbles to be drawn in. This is inherently very inefficient. Furthermore, the prior art of the inlet hopper design is a bulky structure such that in many FCC units there is not enough room to place it. A common

compromise is to use either a straight pipe or an asymmetric hopper for the standpipe inlet which further exacerbates the problems described above.

Standpipe inlet geometry not only affects catalyst circulation, the entrained gas can also have a negative impact on the performance of a stripper of a FCC unit. It is common practice that the stripper includes special trays, such as shown in the invention by Johnson et al in international patent PCT/US95/09335 which is incorporated herein by reference. The special trays in the main vessel enhance the efficiency of hydrocarbon vapor stripping by steam. The spent catalyst is then transported to the regenerator through a stripper standpipe with a hopper inlet as shown in the prior art. The hopper inlet for the stripper standpipe has been shown to be rather ineffective in reducing gas entrainment. The study of Nougier et al in the Second FCC Forum (May 15-17, 1996, The Woodlands, Texas) shows that, even after intensive stripping in the main vessel, the vapor leaving the stripper still contains 20 to 25% by mole (or about 40% by weight) of hydrocarbon products. Gas entrainment from the stripper standpipe into the regenerator has two negative impacts in addition to the impact on catalyst circulation discussed above. First, the entrained gas from the stripper to the regenerator represents a loss in hydrocarbon products which could have been recovered as products. Second, the entrained hydrocarbon has to be burned in the regenerator which consumes limited air available in the regenerator and generates additional heat that has to be removed. Thus, it is essential to reduce gas entrainment into the stripper standpipe.

One configuration of recent prior art, "Fluid Catalytic Cracking Technology and Operation" by Joseph W. Wilson, tries to address the standpipe inlet issue with a design different from the conventional inlet hopper in a large fluidized bed vessel. As will be discussed below with reference to Figure 5, this particular configuration includes a withdrawal well, which is a much smaller fluidized bed vessel, connected to the main regenerator vessel via an inclined duct. The regenerator standpipe is then connected to the bottom of the withdrawal well not having a conventional inlet hopper.

One objective of the instant invention is to reduce gas entrainment into standpipes by a standpipe inlet design. This will lead to increases in overall pressure build-up in the standpipe and catalyst circulation rate as well as improving standpipe stability. The reduction in gas entrainment will also reduce hydrocarbon entrainment from the stripper to the regenerator of a FCC unit, as discussed above. Another objective of the instant invention is to improve catalyst circulation of the prior art of Figure 5 with a withdrawal well having an improved standpipe inlet design.

## SUMMARY OF THE INVENTION

The current invention is a new standpipe inlet design to improve stability of catalyst circulation suitable for applications in catalytic cracking units, fluid cokers and other processes involving circulation of particulate solids between vessels. In a fluid catalytic cracking (FCC) unit, a regenerator, a stripper or a withdrawal well connecting to either of the vessels, includes a standpipe for circulating catalyst from one vessel to another, the standpipe having an inlet design which reduces gas entrainment during catalyst transport by partial de-fluidization in the standpipe inlet region. The standpipe inlet design could include multiple inlet openings, e.g., through the top of the standpipe or from the side wall by means of slots, or both, and a horizontal disk surrounding the standpipe below the slots for blocking the upward flow of bubbles, the combination thereby forming a dense fluidization zone above the disk and surrounding the inlet, including the slots. Additionally, the disk may include a downward-projecting lip or edge forming an inverted void space around the standpipe and the downward-projecting edge may further include vent holes around its circumference which allow bubbles trapped under the disk to be vented outside the standpipe inlet region. Above the disk and surrounding the standpipe, gas injection rings may also be used to prevent the dense fluidization zone above the disk from complete de-fluidization, thus assisting the catalyst to remain fluidized and flow smoothly into the standpipe, either through the slots or at the very top of the open standpipe, or both. The disk itself may also include vent holes for preventing complete de-fluidization. Similar design concepts can be applied to a standpipe connecting to the bottom of a main vessel, such as a regenerator or a stripper, or to the bottom of a withdrawal well connecting to the main vessel.

## BRIEF DESCRIPTION OF THE DRAWINGS

**FIGURE 1** is a sectional view of the lower portion of a regenerator of a FCC unit including a regenerator standpipe.

**FIGURE 2** is an enlarged sectional view of a portion of **Figure 1** of the regenerator standpipe inlet.

**FIGURE 3** is an alternative embodiment of **Figure 2** of the regenerator standpipe inlet.

**FIGURE 4** is another embodiment of the regenerator standpipe inlet when catalyst is drawn from a space near the bottom wall of the regenerator vessel of a FCC unit.

**FIGURE 5** shows an alternate prior art configuration using a withdrawal well.

**FIGURE 6** shows the instant invention which comprises a modification of the standpipe inlet to the prior art configuration of Figure 5.

### **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

5           The main drive for catalyst circulation in FCC units comes from stable and adequate pressure build-up in the standpipe. One critical element of the standpipe design is the inlet design because it determines the inlet condition of the catalyst which, in turn, affects the entire standpipe operation. It is essential to reduce gas entrainment by a properly designed standpipe inlet.

10           The key concept of the instant invention of the standpipe inlet design is totally different from the inlet hopper design of the prior art, which has many disadvantages as discussed previously. The design concept of the instant invention relies on partial de-fluidization, rather than bubble coalescence and growth inside the hopper, to reduce gas entrainment which is discussed in detail below.

15           The reason that FCC catalyst can be maintained at the fluidization state in the regenerator or the stripper is by a continuous supply of upflowing, fluidizing gas. Thus, as soon as the supply of the fluidizing gas is cut off, the fluidized catalyst starts to settle, or de-fluidize, immediately. In the initial stage of this de-fluidization process, bubbles escape very quickly from the fluidized bed, as shown by Khoe et al in Powder Technology Vol. 66 (1991) which is incorporated herein by reference. After the depletion of all bubbles, FCC catalyst can still be maintained at a dense fluidization state for a certain period of time before becoming completely de-fluidized, as also shown by Khoe et al. In Khoe et al's experiments, the de-fluidization process was triggered by shutting off fluidization gas supply, leading to de-fluidization of the entire fluidized bed. However, one could trigger a local de-fluidization  
20 process within a fluidized bed by strategically blocking off the upflowing, fluidizing gas in a selective area. The instant invention of standpipe inlet design utilizes this special characteristic of FCC catalyst by partial de-fluidization in a strategic area to eliminate the bubbles and by allowing only densely fluidized catalyst to flow into the standpipe.

25           **Figure 1** shows a sectional view of the lower portion of a typical regenerator 20 of a FCC unit having a regenerator standpipe 10 which includes an inlet portion 60 to draw in regenerated catalyst according to the instant invention. Spent catalyst is transported from a stripper (not shown) through a typical spent catalyst transport duct 70 and enters the regenerator 20 where coke deposition on catalyst is burned off by air which is supplied by

main air grid 30. The air from grid 30 and the resulting combustion gas rise through the regenerator, thus keeping the catalyst fluidized in fluidized bed 40. The combustion gas and entrained regenerated catalyst are separated in the upper part of the regenerator by cyclones (not shown). The combustion gas exits from the upper part of the regenerator and the regenerated catalyst, separated by cyclones (not shown), is returned to the fluidized bed 40. Typical density of the fluidized bed 40 in regenerator 20 is in the range of 20 to 40 lb/ft<sup>3</sup>, with the presence of many rising gas bubbles. The density of the fluidized bed 40 is controlled mainly by the air flow from air grid 30 where higher fluidizing air flow leads to more gas bubbles and lower density of fluidized bed 40. The fluidized bed 40 is maintained at a certain level 50 by a slide valve (not shown), or other means, located at the bottom of the regenerator standpipe 10 to control the rate of regenerated catalyst being drawn into regenerator standpipe 10. The top of the regenerator standpipe 10, including a standpipe inlet 60 according to the instant invention, is shown as enclosed by the dotted circle, is completely submerged in the fluidized bed 40 inside regenerator 20. Although the standpipe 10 is shown in Figure 1 to be vertical and protruding into regenerator 20 from the bottom, the instant invention of the standpipe inlet 60 can be applied to other configurations where the standpipe 10 might protrude into regenerator 20 through the side wall, instead of the bottom, and it might be inclined, instead of vertical.

Referring now to Figure 2 for the details of standpipe inlet 60 in Figure 1, the regenerator standpipe 10 is typically a cylindrical duct with a diameter in the range of about 1 to about 5 feet. Regenerated catalyst is drawn into the standpipe 10 through one of two types of openings, or both, according to the instant invention. The first is the top opening 11 of the standpipe and the second is a plurality of openings 12 cut through the walls of the upper portion of the standpipe 10. Although slots are shown in Figure 2 for openings 12, other forms, such as circular holes, could also be used. Below the openings 11 and 12 is a horizontal disk 13 surrounding the standpipe 10. In the following discussion, the element 13 will be referred to as a "disk", which is the most logical form for a cylindrically-shaped vessel. It will be appreciated, however, that the element 13 may simply be a plate of any desired shape. Since the entire standpipe inlet is submerged in the fluidized bed 40 where catalyst is fluidized by the continuous upflow of fluidizing gas from air grid 30 (see Fig. 1), disk 13 strategically blocks off the supply of the fluidizing gas coming from below and triggers the local de-fluidization process in the region directly above disk 13. As fully fluidized regenerated catalyst together with gas bubbles are being drawn toward the standpipe openings 11 and 12, the fluidizing gas is blocked off by disk 13 (except as described below)

and bubbles migrating toward standpipe openings **11** and **12** run out of the continuous supply of fluidizing gas very quickly. This creates a dense fluidized zone **14**, shown enclosed by the dotted line in **Figure 2**, with almost no bubble presence in the near proximity to the standpipe openings **11** and **12**. This allows catalyst to partially de-fluidize by eliminating gas bubbles before entering standpipe **10**, but not to the extent of complete de-fluidization where catalyst can no longer flow. To prevent complete de-fluidization in the dense fluidization zone **14** above the disk **13**, a small gas flow can be supplied, either by vent holes **13c** in the disk **13** or through a gas injection ring **15** located above the disk **13**. Although a gas injection ring **15** is shown in **Figure 2**, other means, such as a gas injection grid, can also be used to achieve the same objective of preventing complete de-fluidization in the dense fluidization zone **14** above the disk **13**. The disk **13** may include a downwardly-projecting side or lip **13a** which circles the disk **13**, preferably at its circumference. The void below disk **13** surrounded by lip **13a** allows the disk to capture fluidizing gas coming from below. To continuously vent off the fluidizing gas, lip **13a** may further include a plurality of vent holes **13b** which allows fluidizing gas to be vented off outside the dense fluidization zone **14**. Alternatively, a vent tube **16** may be used to discharge fluidizing gas from below the disk **13** to a location above the dense fluidization zone **14**. Although a horizontal disk **13** is proposed as one means to achieve local de-fluidization in the dense fluidization zone **14** in **Figure 2**, other means can be applied to achieve the same objective. One such alternative is shown in **Figure 3**.

Referring now to **Figure 3**, regenerated catalyst is again drawn into the standpipe **10'** through the top opening **11'**, or a plurality of openings **12'**, or both. Instead of using a horizontal disk **13** as in **Figure 2**, **Figure 3** shows that below the openings **11'** and **12'** is a conical disk **13'** surrounding the standpipe **10'**. The function of the conical disk **13'** is to strategically block off the supply of the fluidizing gas coming from below and to trigger the local de-fluidization process in the region directly above disk **13'**. This creates a dense fluidized zone **14'**, enclosed by the dotted line in **Figure 3**. To prevent complete de-fluidization in the dense fluidization zone **14'**, a small gas flow can be supplied, either by vent holes **13c'** in the disk **13'** or through a gas injection ring **15'** located above the disk **13'**. Although a gas injection ring **15'** is shown in **Figure 3**, other means, such as a gas injection grid, can also be used to achieve the same objective of preventing complete de-fluidization in the dense fluidization zone **14'** above the disk **13'**. The void below conical disk **13'** allows the disk to capture fluidizing gas coming from below. To continuously vent off the accumulation of the fluidizing gas, disk **13'** may further include a plurality of vent holes with extension pipes **13b'** which allows fluidizing gas to be vented off outside the dense

fluidization zone 14'. Alternatively, a vent tube 16' may be used to discharge fluidizing gas from below the disk 13' to a location above the dense fluidization zone 14'. One advantage of the conical disk 13' over the horizontal disk 13 in **Figure 2** is that catalyst is less likely to become stagnant when gas flow from the gas injection ring 15' is turned off.

**Figure 4** shows another embodiment of a regenerator standpipe inlet using a design similar to the concept of **Figure 1** except when the FCC process prefers to draw regenerated catalyst from a region very close to the bottom of regenerator 120. Spent catalyst is transported from a stripper (not shown) through a spent catalyst transport duct 170 and enters the regenerator 120. The regenerated catalyst is separated from flue gas in the upper part of the regenerator by cyclones (not shown). The flue gas exits from the upper part of the regenerator and the regenerated catalyst separated by cyclones (not shown) is returned to the lower part of the regenerator 120 to form the fluidized bed 140 by the continuous upflow of fluidizing air and combustion gas from air grid 130. The fluidized bed 140 is maintained at a level 150 by a slide valve (not shown), or other means, located at the bottom of the regenerator standpipe 110 to control the rate of regenerated catalyst being drawn into the regenerator standpipe 110. The regenerator standpipe 110 still has one of two types of inlet openings, or both, to draw catalyst from the fluidized bed 140 of the regenerator. The first opening is the top opening 111 of the standpipe 110 and the second is a plurality of openings 112 cut through the walls of the upper portion of the standpipe 110 just above the bottom vessel wall 113 of regenerator 120. Although the standpipe 110 is shown in **Figure 4** to be vertical, the instant invention of the standpipe inlet can also be applied to other configurations where the standpipe 110 might be inclined. The function of the bottom wall 113 in **Figure 4** is similar to that of the disk 13 in **Figure 2**, i.e., to induce local de-fluidization and to create a dense fluidization zone 114 (as in zone 14 of **Fig. 2**) with almost no bubbles present in the near proximity to the standpipe openings 111 and 112. To prevent complete de-fluidization near the vessel wall, a small gas flow can be supplied through a gas injection ring 115. Although a gas injection ring 115 is shown in **Figure 4**, other means, such as a gas injection grid, can also be used to achieve the same objective of preventing complete de-fluidization in the dense fluidization zone 114 above the vessel wall 113.

A regenerator standpipe inlet according to **Figure 4** was installed in one of Assignee's FCC units which originally had a hopper standpipe inlet of the prior art design. The original inlet hopper was removed and four slots measuring 6 inches wide by 40 inches long were created on the standpipe wall. After the installation of the new regenerator standpipe inlet, catalyst circulation rate of the FCC unit was increased by 30%, with an

additional 3 psi pressure build-up in the regenerator standpipe. This was a clear indication that the standpipe inlet of the instant invention was very effective in reducing gas entrainment from the regenerator thus allowing the standpipe to run at higher density and to build more pressure for increasing catalyst circulation. Furthermore, the standpipe operation became more stable even at a higher catalyst circulation rate compared to previous operation.

“Fluid Catalytic Cracking Technology and Operation” by Joseph W. Wilson shows another prior art configuration which tries to address the standpipe inlet issue with a design which is different from the conventional inlet hopper located inside a large fluidized bed vessel. As shown in Figure 5, this particular configuration includes a withdrawal well 51 located beside the regenerator 52 (analogous to regenerator 20 of Figure 1). The withdrawal well 51 is a much smaller vessel compared to the regenerator 52. . The withdrawal well 51 connects to the main regenerator 52 via an inclined standpipe 53 to allow catalyst to flow from the regenerator 52 to the withdrawal well 51. The overhead of the withdrawal well 51 is connected to the regenerator 52 via a vent line 55 to allow gas in the withdrawal well 51 to flow back to the dilute phase of the regenerator vessel above the regenerator 52 fluidized bed 58 (analogous to regenerator fluidized bed 40 of Figure 1). The regenerator standpipe 56 (analogous to standpipe 10 of Figure 1) is connected to the bottom of the withdrawal well 51 to allow catalyst to be transferred to the reactor 100 in the usual manner. The withdrawal well has its own fluidization injection 54 near the bottom of the withdrawal well 51 and close to the inlet 56’ of regenerator standpipe 56. The fluidization injection 54 controls the fluidization condition of the withdrawal well 51 and maintains a fluidized bed level 57, which is lower than the regenerator bed level 58. The difference in elevation between the regenerator bed level 58 and the withdrawal well bed level 57 allows catalyst to flow through the inclined standpipe pipe 53.

According to the open literature, such as the paper entitled “Controlling Gas Flow in Standpipe Systems” by T. A. Gauthier and J. L. Ross presented at the 1998 Annual meeting of the AIChE, the key concept of the prior art of the withdrawal well in Figure 5 is not to withdraw catalyst directly from the main regenerator vessel 52, which is highly fluidized with a density in the range of 20 to 40 lb/ft<sup>3</sup> with the presence of many rising gas bubbles, because excess gas (bubbles) would enter the standpipe under such conditions when using a conventional inlet hopper. A key concept, according to Gauthier and Ross, is that catalyst flowing from the regenerator 52 into the withdrawal well 51 should be slow enough for bubbles to rise in the withdrawal well 51. The gas in the withdrawal well 51 can flow back to the regenerator 52 via vent line 55. The catalyst condition in the withdrawal well 51 is

controlled independently by fluidization injection 54. Another key concept of the withdrawal well, according to Gauthier and Ross, is to reach an ideal condition for the catalyst near minimum bubbling condition when entering the standpipe 56.

However, reaching such an ideal condition for the catalyst in the withdrawal well is difficult using the prior art configuration of Figure 5. According to T. A. Gauthier and J. L. Ross's paper, under certain conditions the withdrawal well could lead to partial de-fluidization and poor catalyst circulation. The de-fluidization is due, at least in part, to the fluidization injection 54 being located close to the standpipe 56 inlet 56'. When part of the fluidization gas emitted from fluidization injection 54 is drawn into the standpipe 56 by the catalyst circulation, the withdrawal well 51 could partially lose its fluidization, or become partially de-fluidized, which leads to catalyst circulation difficulty.

One of Assignee's FCC units originally had a withdrawal well of the prior art similar to Figure 5. This FCC unit had experienced difficulties in maintaining stable catalyst circulation due to standpipe instability. The standpipe instability was most severe not only at high catalyst circulation rates but also at low rates. During four years, this FCC unit experienced standpipe operational problems, which led to several unit feed outages and disruptions to the entire refinery. In addition, the standpipe instability was very sensitive to the change of the regenerator bed level, which severely restricted the flexibility of the FCC operation.

Figure 6 shows the regenerator withdrawal well 51 of Figure 5 as modified by the instant invention. As shown in Figure 6, the regenerator 52, the inclined standpipe 53, the vent line 55 connecting the regenerator 52 to the withdrawal well 51 and the regenerator standpipe 56 remain the same. The modifications provided by the instant invention include an extended standpipe section 70, which extends into the withdrawal well 51, and a new fluidization injection 72 located close to the upper end of the extended standpipe section 70. The extended standpipe 70 has an open upper end 56' inside the withdrawal well, near the level of the fluidization injection 72, to allow fluidized catalyst to flow into standpipe 56. In addition, the extended standpipe 70 also includes a plurality of elongated slot openings 71, at a level near or below the fluidization injection 72, to provide additional passages for catalyst to flow into standpipe 56. The number of elongated slot openings could be in the range of one to twenty, but is preferably in the range of two to eight. The total flowing area of the elongated slot openings could be in the range of 20% to 800% of the area of standpipe inlet 56' opening, but is preferably in the range of 50% to

400%. The fluidization injection 72 may include one or a plurality of gas injection conduits which have a plurality of nozzles injecting fluidization gas both upward and downward. The upward fluidization velocity emitted from the fluidization injection 72, based on the cross-sectional area of the withdrawal well at its largest diameter, could be in the range of 0.05 to 4 feet/sec, but is preferably in the range of 0.2 to 2 feet/sec. The downward fluidization velocity emitted from the fluidization injection 72, based on the largest cross-sectional area of the withdrawal well, could be in the range of 0 to 2 feet/sec, but is preferably in the range of 0.02 to 1 feet/sec. The fluidization injection 72 of the instant invention is located at a higher elevation compared to the fluidization injection 54 in Figure 5 of the prior art. The combination of the fluidization injection 72 and the extended standpipe section 70 having a plurality of elongated slots 71 reduces gas entrainment into the standpipe 56, thus allowing withdrawal well 51 to maintain a fluidized condition at all time. This assures smooth catalyst circulation.

Since installation of the modifications with the instant invention according to Figure 6, Assignee's FCC unit has been running in a stable mode in the entire range of catalyst circulation rates, which is quite different from the previous operational experience with the prior art configuration of Figure 5. There has been no instance of feed outage caused by standpipe instability since modification of the FCC with the instant invention. In addition, the highest catalyst circulation rate has been increased by 15%, compared to the prior art of Figure 5. The unit also became less sensitive to the change of regenerator level, which allows the unit to operate in a wider range of conditions

From the discussion above, it is demonstrated that the standpipe inlet design of the instant invention has several advantages over the inlet hopper design of the prior art when it is applied to the regenerator standpipe of a FCC unit:

**More Stable Operation** – The inlet design of the instant invention does not rely on the mechanism of the prior art inlet hopper to draw in lots of bubbles, letting them coalesce and grow into large bubbles. Instead, the new inlet design minimizes bubble entrainment by strategically eliminating bubbles around the standpipe inlet region with local de-fluidization. Since the new design does not require the formation and release of large bubbles in the hopper design, which leads to standpipe instability, the design of the instant invention is inherently more stable.

**More effective in reducing gas entrainment** – The concept of the prior art inlet hopper is to draw in lots of bubbles while trying to reduce gas entrainment. This is inherently

a very inefficient design. On the other hand, the basic design of the instant invention is to strategically eliminate bubbles by local de-fluidization of the catalyst before it enters the standpipe. Thus, the design of the instant invention is inherently more efficient in reducing gas entrainment into the standpipe.

5           Better Control – The prior art hopper inlet has little control of gas entrainment around the inlet. As the catalyst circulation rate increases, more and more bubbles are drawn into the hopper, leading to higher and higher gas entrainment. The design of the instant invention, on the other hand, maintains complete control of the flow condition near the inlet by eliminating all bubbles, then introducing only a small amount of gas necessary for smooth  
10 operation.

          Simplicity – The design of the instant invention is simpler and more robust than the prior art hopper design.

          When the standpipe inlet design of the instant invention is applied to the stripper standpipe, it provides several additional advantages over the prior art inlet hopper  
15 design for enhancing stripper and regenerator performance of a FCC unit. This is in addition to the benefits already discussed for application in the regenerator standpipe where catalyst circulation and standpipe stability are the main concerns:

          Higher stripping efficiency – The standpipe inlet design of the instant invention is shown to be more effective in reducing gas entrainment into the standpipe. Since  
20 the entrained gas from the stripper standpipe may contain about 40% by weight of hydrocarbon products, the standpipe inlet design of the instant invention effectively increases hydrocarbon products by reducing hydrocarbon loss to the gas entrainment.

          Lower regenerator loading – Since the stripper standpipe inlet design of the instant invention is more effective in reducing gas entrainment, less hydrocarbon will enter  
25 the regenerator. This leads to lower air requirement and less heat to be removed as less hydrocarbon is to be burned in the regenerator. More importantly, many FCC units today are limited by air supply or heat removing capacity in the regenerator. Thus, the instant invention can be used to debottleneck the unit.

          When the standpipe inlet design of the instant invention is applied to the  
30 withdrawal well of the prior art, it has been demonstrated that the modification has several advantages:

          More Stable Operation – The inlet design of the instant invention eliminates the problems of local de-fluidization of the original withdrawal well of the prior art. This leads to a more stable catalyst flow at all conditions.

More flexibility – The standpipe operation is no longer sensitive to the regenerator bed level which gives more flexibility to operate the unit.

Higher catalyst circulation – The modification leads to 15% higher catalyst circulation.

- 5            Although the above discussion focuses on the applications of the instant invention in FCC units, a similar standpipe inlet design can also be applied to improve circulation of particulate solids and reduce gas entrainment in other petrochemical processes, such as fluid cokers and flexicokers, and processes other than petrochemical, such as circulating fluidized bed combustors, where large quantities of particulate solids are
- 10            circulated between different vessels connected by standpipes and risers.

**WHAT IS CLAIMED IS:**

1. In a catalytic cracking unit comprising:

a regenerator;

a catalyst withdrawal well spaced from said regenerator;

a downwardly inclined standpipe having its upper end fluidly connected to said regenerator, and its lower end fluidly connected to said catalyst withdrawal well;

a standpipe for receiving catalyst from said catalyst withdrawal well, said standpipe having an open end fluidly connected to said catalyst withdrawal well, the improvement comprising:

an inlet portion of said standpipe extending into said catalyst withdrawal well for receiving and transporting said catalyst from said catalyst withdrawal well, said extended standpipe inlet portion including an open upper end and a plurality of openings cut through the wall of said extended standpipe below said open upper end and above the floor of said catalyst withdrawal well.

2. The apparatus of Claim 1 wherein said plurality of openings are slots.

3. The apparatus of Claim 1 further including means for injecting fluidizing gas above said floor of said catalyst withdrawal well for maintaining fluidization of said particulate solids in said catalyst withdrawal well.

4. The apparatus of Claim 1 wherein said standpipe is part of a withdrawal well of a fluid catalytic cracking unit.

5. The apparatus of Claim 1 wherein said standpipe is part of a stripper of a fluid catalytic cracking unit.

6. The apparatus of Claim 1 wherein said standpipe is part of a regenerator of a fluid catalytic cracking unit.

7. The apparatus of Claim 2 wherein said standpipe is part of a withdrawal well of a fluid catalytic cracking unit.

8. The apparatus of Claim 2 wherein said standpipe is part of a stripper of a fluid catalytic cracking unit.

9. The apparatus of Claim 2 wherein said standpipe is part of a regenerator of a fluid catalytic cracking unit.

10. The apparatus of Claim 3 wherein said means for injecting fluidizing gas includes at least one gas injection ring.
11. The apparatus of Claim 3 wherein said standpipe is part of a withdrawal well of a fluid catalytic cracking unit.
12. The apparatus of Claim 3 wherein said standpipe is part of a stripper of a fluid catalytic cracking unit.
13. The apparatus of Claim 3 wherein said standpipe is part of a regenerator of a fluid catalytic cracking unit.
14. The apparatus of Claim 4 wherein said standpipe is part of a withdrawal well of a fluid catalytic cracking unit.
15. The apparatus of Claim 4 wherein said standpipe is part of a stripper of a fluid catalytic cracking unit.
16. The apparatus of Claim 4 wherein said standpipe is part of a regenerator of a fluid catalytic cracking unit.
17. The apparatus of Claim 10 wherein said at least one gas injection ring is located at a level near said open upper end of said extended standpipe inlet.
18. The apparatus of Claim 17 wherein said standpipe is part of a withdrawal well of a fluid catalytic cracking unit.
19. The apparatus of Claim 17 wherein said standpipe is part of a stripper of a fluid catalytic cracking unit.
20. The apparatus of Claim 17 wherein said standpipe is part of a regenerator of a fluid catalytic cracking unit.
21. In a hydrocarbon process unit comprising:
  - a main fluidized bed vessel with particulate solids;
  - a withdrawal well spaced from said main fluidized bed vessel;
  - a downwardly inclined standpipe having its upper end fluidly connected to said main fluidized bed vessel, and its lower end fluidly connected to said withdrawal well;
  - a standpipe for receiving particulate solids from said withdrawal well, said standpipe having an open end fluidly connected to said withdrawal well, the improvement comprising:
    - an inlet portion of said standpipe extending into said withdrawal well for receiving and transporting said particulate solids from said withdrawal well, said extended standpipe inlet portion including an open upper end and a plurality of openings cut through the wall of said extended standpipe below said open upper end and above the floor of said withdrawal well.

22. The apparatus of Claim 21 wherein said plurality of openings are slots.
23. The apparatus of Claim 21 further including means for injecting fluidizing gas above said floor of said withdrawal well for maintaining fluidization of said particulate solids in said withdrawal well.
24. The apparatus of Claim 23 wherein said means for injecting fluidizing gas includes at least one gas injection ring.
25. The apparatus of Claim 24 wherein said at least one gas injection ring is located at a level near said open upper end of said extended standpipe inlet.

20110711 11:00 AM

5

## ABSTRACT OF THE DISCLOSURE

### STANDPIPE INLET FOR ENHANCING PARTICULATE SOLIDS CIRCULATION FOR PETROCHEMICAL AND OTHER PROCESSES

10

In a fluid catalytic cracking (FCC) unit, a regenerator, a stripper or a withdrawal well connecting to either of the vessels, includes a standpipe for circulating catalyst from one vessel to another, the standpipe having an inlet design which reduces gas entrainment during catalyst transport by partial de-fluidization in the standpipe inlet region. The standpipe inlet design could include multiple inlet openings through the top of the standpipe or from the side wall by means of slots, or both, and a horizontal disk surrounding the standpipe below the slots for blocking the upward flow of bubbles, the combination thereby forming a dense fluidization zone above the disk and surrounding the inlet, including the slots. Additionally, the disk may include a downwardly-projecting lip or edge forming an inverted void space around the standpipe and the downwardly-projecting edge may further include vent holes around its circumference which allow bubbles trapped under the disk to be vented outside the standpipe inlet region. Above and below the disk and surrounding the standpipe, gas injection rings may be used to prevent the dense fluidization zone above the disk from complete de-fluidization, thus assisting the catalyst to remain fluidized and flow smoothly into the standpipe either through the slots or at the very top of the open standpipe, or both.

25

30

1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2443	2444
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------



TH1781




FIG 2

TH781




FIG. 3

TH1781





FIG. 4

[illegible]

TH1781




FIG. 6

# DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

ATTORNEY'S DOCKET NO.  
TH1781 (US)

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled : **STANDPIPE INLET FOR ENHANCING PARTICULATE SOLIDS CIRCULATION FOR PETROCHEMICAL AND OTHER PROCESSES** the specification of which is attached hereto unless the following box is checked:

☐ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ ( if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 27 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

## PRIOR FOREIGN APPLICATION(S)

APPLICATION NUMBER	COUNTRY	DAY/MONTH/YEAR FILED
APPLICATION NUMBER	COUNTRY	DAY/MONTH/YEAR FILED

Priority  
Not Claimed

☐  
☐

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

APPLICATION SERIAL NO.	FILING DATE
APPLICATION SERIAL NO.	FILING DATE

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) or § 365(c) of any PCT International application designating the United States, listed below and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

APPLICATION SERIAL NO.	FILING DATE	STATUS-PATENTED, PENDING, ABANDONED
APPLICATION SERIAL NO.	FILING DATE	STATUS-PATENTED, PENDING, ABANDONED

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

NAME	ATTORNEY/AGENT	REGISTRATION NUMBER	TELEPHONE NUMBER
Carl O. McClenny	Attorney	26,481	(713) 782-3620
NAME	ATTORNEY/AGENT	REGISTRATION NUMBER	TELEPHONE NUMBER
Dean F. Vance	Attorney	27,603	(713) 241-3716

Revised

June 1995

## SEND CORRESPONDENCE TO:

(NAME) Carl O. McClenny  
c/o Shell Oil Company  
Intellectual Property  
P.O. Box 2463  
Houston, TX 77252-2463

# DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

ATTORNEY'S DOCKET NO.  
TH1781 (US)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR (given name, family name) <b>Ye-Mon CHEN</b>	
INVENTOR'S SIGNATURE	DATE SIGNED
RESIDENCE <b>2215 Bent River Drive, Sugar Land, Texas 77479</b>	CITIZENSHIP <b>United States</b>
POST OFFICE ADDRESS <b>2215 Bent River Drive, Sugar Land, Texas 77479</b>	

FULL NAME OF SECOND JOINT INVENTOR, IF ANY (given name, family name)	
SECOND INVENTOR'S SIGNATURE	DATE SIGNED
RESIDENCE	CITIZENSHIP
POST OFFICE ADDRESS	

FULL NAME OF THIRD JOINT INVENTOR, IF ANY (given name, family name)	
THIRD INVENTOR'S SIGNATURE	DATE SIGNED
RESIDENCE	CITIZENSHIP
POST OFFICE ADDRESS	

FULL NAME OF FOURTH JOINT INVENTOR, IF ANY (given name, family name)	
FOURTH INVENTOR'S SIGNATURE	DATE SIGNED
RESIDENCE	CITIZENSHIP
POST OFFICE ADDRESS	

FULL NAME OF FIFTH JOINT INVENTOR, IF ANY (given name, family name)	
FIFTH INVENTOR'S SIGNATURE	DATE SIGNED
RESIDENCE	CITIZENSHIP
POST OFFICE ADDRESS	